



FUEL SYSTEM

POS.	CODE	DESCRIPTION	Qty
1	«-----»	locking nut	0
7	9080.262	end pipe	1
8	3630.069	clamp	1
9	3790.070	flange	2
10	3240.163	nut M 8	4
11	6780.086	stud M 8 X 65 (77)	4
12	9346.029	bleeding pipe	1
13	9571.204	bleeding pipe mm 330	1
14	5400.046	rubber sheathing	2
15	9865.122	screw M 6 X 12	1
16	3206.045	nut	2
17	7565.013	washer diam.12	2
18	1790.027	bolt M 12 X 1,25 X 20	2
19	8865.091	support	1
20	3240.020	nut M 8	2
21	3240.018	nut M 8	2
22	7565.007	washer diam. 8	2
23	7625.012	washer diam. 8,4	2
24	8635.059	vibration-damping	2
25	9043.092	fuel tank cap	1
26	7565.007	washer diam. 8	2
27	3240.018	nut M 8	2
28	3240.020	nut M 8	2
30	4906.008	fuel gauge (mm 193) 15/29 lt	1
31	«-----»	union	0
35	4670.009	copper gasket 0,50	2
35	4670.010	copper gasket 1,00	2
36	6615.085	nozzle-holder	2
37	6531.432	nozzle	2
39	3616.018	injector feed pipe saddle	2
40	8545.476	brace	1
41	3240.020	nut M 8	2
42	8866.002	tank support	1
43	1780.003	bolt M 10 X 1,5 X 18	2
44	7565.011	washer diam.10	2
45	7980.042	cup	2
46	7625.012	washer diam. 8,4	2
47	7565.007	washer diam. 8	2
48	8960.012	buffer	2
49	6487.004	pivot	2
50	4670.059	copper gasket diam.10	2
51	1901.045	union bolt M 10	1
52	8101.032	Fuel tank	1
52	8102.063	FUEL TANK fitted for level gauge	1
53	9372.003	fuel pipe	1
57	«-----»	union bolt	0
64	1901.101	union bolt l=60	1
65	4670.062	copper gasket diam. 6,2 X 10 X 1,5	2
66	1901.033	union bolt M 6	1
67	«-----»	fuel hose	0
68	9375.827	high.p.pipe (1° cil)	1
70	9375.826	high.p.pipe (2° cil)	1
73	4670.060	copper gasket diam.12	2

Group: 5LD
Engine: 5LD 825-2 Drawing: E

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
84	3730.121	fuel filter	1
87	1901.171	deaeration plug	1
88	4775.196	gasket	1
89	9372.060	fuel pipe	1
90	1901.031	union bolt M 12	1
91	4670.060	copper gasket diam.12	2
92	7625.010	washer diam. 8	4
93	9732.074	screw M 8 X 20	4
94	4670.060	copper gasket diam.12	1
95	9080.035	cap	1
96	3587.103	el.valve (12V) on injection pump	1
97	3203.050	selflocking nut M 6	2
98	«-----»	angle bracket	0
99	7625.070	washer diam. 6	2
100	1760.005	bolt M 6 X 1 X 16	2
101	«-----»	fuel hose	0
103	3587.105	el.valve 12V on engine	1
104	1901.030	union bolt M 10	1
105	4670.059	copper gasket diam.10	2
110	1780.005	bolt M 10 X 1,5 X 28	2
111	1901.032	union bolt M 14	1
112	4670.061	copper gasket diam.14	2
113	771R.001	washer diam. 5,3	1
114	6590.034	injection pump	1
115	4580.002	gasket 0,10	4
115	4580.009	gasket 0,50	1
115	4580.068	gasket 0,05	1
116	1580.023	bushing	1
117	2800.003	cotter pin	1
120	7265.008	connection	2
121	7470.003	filler	2
122	1200.031	rubber oil seal	2
133	7555.008	washer diam.10	2
134	3730.151	fuel filter	1
135	2175.046	fuel filter cartridge	1
136	4670.061	copper gasket diam.14	2
137	1901.032	union bolt M 14	1
138	9375.029	fuel hose(mm 835)	1
139	6585.051	feed pump	1
140	4670.059	copper gasket diam.10	2
142	1901.030	union bolt M 10	1
143	«-----»	pin	0
144	5755.034	valve spring	2
145	9672.012	delivery valve BOSCH	2
146	6578.013	injection plunger	2
147	8335.029	washer seal	2
148	4760.015	valve gasket	2
149	8400.048	taper pin	1
157	1901.030	union bolt M 10	1
158	4670.059	copper gasket diam.10	2
159	7200.042	drive rod	1
160	4580.169	gasket 0,40	1
160	4580.170	gasket 0,80	1

Group: 5LD
Engine: 5LD 825-2 Drawing: E

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
162	«-----»	stud M 8 X 20 (32)	0
163	3203.093	nut M 8	2
164	4850.009	guide	1
166	5625.002	spring	2
167	7980.020	cup	2
169	«-----»	no longer available - see pos. 114/118	0
171	6230.069	pin	1
172	«-----»	see Pos. 114/118	0
187	3586.058	electric valve	1
188	3440.056	QSD STOP DEVICE 12V	1
189	2175.046	fuel filter cartridge	1
190	6230.068	pin	2
191	«-----»	see Pos. 193	0
193	7215.017	tappet	2
194	«-----»	spring retainer bottom - see Pos. E114	0

E
5LD

