

**LOMBARDINI**

A KOHLER COMPANY

Group: 6LD

Engine: 6LD 400 Drawing: F

**COOLING SYSTEM/STARTING**

| POS. | CODE     | DESCRIPTION                                                     | Qty |
|------|----------|-----------------------------------------------------------------|-----|
| 2    | 5066.198 | airtight plate                                                  | 1   |
| 3    | 5066.199 | airtight plate                                                  | 1   |
| 4    | 6370.302 | plate (for rope or rewind starting)                             | 1   |
| 5    | 4570.010 | gasket                                                          | 1   |
| 6    | 2569.058 | shroud std                                                      | 1   |
| 6    | 2569.277 | shroud fitted for pulley guard                                  | 1   |
| 6    | 2569.560 | shroud fitted for rewind starting                               | 1   |
| 7    | 2670.022 | pulley cover                                                    | 1   |
| 8    | 6370.128 | plate for starting motor                                        | 1   |
| 9    | 8460.083 | lockpin                                                         | 1   |
| 10   | 4570.014 | gasket                                                          | 2   |
| 11   | 1760.001 | bolt M 6 X 1 X 10                                               | 2   |
| 12   | 7565.004 | washer diam. 6                                                  | 2   |
| 13   | 1585.058 | ball bearing                                                    | 2   |
| 14   | 8430.019 | lockpin                                                         | 1   |
| 15   | 1202.016 | O ring 109                                                      | 1   |
| 16   | 8965.031 | grease plug                                                     | 1   |
| 18   | 5725.043 | spring                                                          | 1   |
| 19   | 6927.270 | shroud panel                                                    | 1   |
| 20   | 3203.050 | selflocking nut M 6                                             | 1   |
| 21   | 1760.093 | bolt M 6 X 1 X 85                                               | 1   |
| 22   | «-----»  | gear                                                            | 0   |
| 23   | 2568.098 | shroud                                                          | 1   |
| 24   | 2690.145 | cover                                                           | 1   |
| 25   | 4970.012 | gear                                                            | 1   |
| 26   | 7885.026 | housing                                                         | 1   |
| 27   | 7555.029 | washer diam. 8                                                  | 3   |
| 28   | 1770.005 | bolt M 8 X 1,25 X 22                                            | 3   |
| 29   | 5801.027 | spring                                                          | 1   |
| 30   | 7980.045 | cup                                                             | 1   |
| 31   | 1240.041 | circlip                                                         | 1   |
| 32   | 6745.050 | oil switch 0,3 bar (M 12)                                       | 1   |
| 33   | 6491.013 | pipe elbow                                                      | 1   |
| 34   | 9790.037 | screw M 6 X 8                                                   | 2   |
| 35   | 7565.007 | washer diam. 8                                                  | 2   |
| 36   | «-----»  | pulley                                                          | 0   |
| 36   | 6960.069 | pulley                                                          | 1   |
| 37   | 1765.053 | bolt M 7 X 1 X 24                                               | 4   |
| 38   | 4055.045 | rope starting                                                   | 1   |
| 42   | «-----»  | circlip                                                         | 0   |
| 43   | 5660.066 | recovery spring                                                 | 1   |
| 44   | 5025.097 | tooth                                                           | 1   |
| 45   | 5455.006 | hand-crank                                                      | 1   |
| 46   | «-----»  | see Pos. D 111                                                  | 0   |
| 47   | 4670.014 | copper gasket diam.12                                           | 1   |
| 48   | 3617.046 | clamp                                                           | 1   |
| 49   | 6275.093 | safety plate                                                    | 1   |
| 51   | «-----»  | deflector                                                       | 0   |
| 51   | 3350.090 | deflector for hand starting                                     | 1   |
| 52   | 7362.228 | voltage regulator. 12V 14/26A-6 contacts for alternator 3 wires | 1   |
| 52   | 7362.298 | voltage regul.12 V maX 30 A - 5 contacts for alt.2 wires        | 1   |
| 54   | 2568.078 | shroud                                                          | 1   |
| 54   | 2569.116 | shroud                                                          | 1   |

**Group: 6LD**  
**Engine: 6LD 400 Drawing: F**

| COOLING SYSTEM/STARTING |          |                                                                 |     |
|-------------------------|----------|-----------------------------------------------------------------|-----|
| POS.                    | CODE     | DESCRIPTION                                                     | Qty |
| 54                      | 2569.563 | shroud                                                          | 1   |
| 56                      | 7330.019 | oil switch connector                                            | 1   |
| 57                      | 4670.058 | copper gasket diam. 8,2X12X1,5                                  | 1   |
| 58                      | 1901.048 | union bolt M 8                                                  | 1   |
| 59                      | 1156.098 | volt.alternator 12V 4A (70W) - 2 wires                          | 1   |
| 59                      | 1157.154 | volt.alternator 12V 14A - 3 wires                               | 1   |
| 59                      | 1157.167 | volt.alternator 12V 16A - 2 wires                               | 1   |
| 60                      | 1760.042 | bolt M 6 X 1 X 18                                               | 6   |
| 60                      | 9730.015 | screw M 6 X 30                                                  | 5   |
| 61                      | 7565.004 | washer diam. 6                                                  | 6   |
| 62                      | 7555.004 | washer diam. 6                                                  | 4   |
| 63                      | 9730.012 | screw M 6 X 20                                                  | 4   |
| 63                      | 9731.022 | screw M 5 X 20                                                  | 4   |
| 64                      | 6740.153 | inlet regul.Saprisa                                             | 1   |
| 65                      | 6607.015 | rectifier bridge                                                | 1   |
| 65                      | 7362.232 | light.alt.regul.-5 contacts for alt. 3 wires                    | 1   |
| 66                      | 5840.142 | starting motor                                                  | 1   |
| 66                      | 5840.211 | starting motor 24V 2,5 KW (BOSCH)                               | 1   |
| 67                      | 3790.040 | flange                                                          | 1   |
| 68                      | 8335.073 | spacer                                                          | 1   |
| 69                      | «-----»  | cover                                                           | 0   |
| 70                      | 5590.026 | thrust spring                                                   | 1   |
| 71                      | 5025.097 | tooth                                                           | 1   |
| 74                      | 7980.067 | cup                                                             | 1   |
| 75                      | 7100.377 | recoil pulley                                                   | 1   |
| 76                      | 4904.038 | handle ass.y                                                    | 1   |
| 77                      | 5801.539 | spiral spring                                                   | 1   |
| 78                      | 5041.020 | key switch                                                      | 1   |
| 79                      | 7245.417 | dashboard 3 warning lights                                      | 1   |
| 79a                     | 7245.422 | dashboard 2 warning lights with internal rectifier bridge (4V v | 1   |
| 80                      | «-----»  | see Pos. F83 (with rewind starting)                             | 0   |
| 83                      | 3527.391 | spacer                                                          | 1   |
| 84                      | 3203.050 | selflocking nut M 6                                             | 1   |
| 85                      | 7625.007 | washer diam. 6                                                  | 1   |
| 86                      | 3527.357 | spacer                                                          | 1   |
| 87                      | 8545.500 | brace                                                           | 1   |
| 88                      | 1760.007 | bolt M 6 X 1 X 25                                               | 1   |
| 89                      | 9732.037 | screw M 10 X 40                                                 | 2   |
| 90                      | 5111.095 | plate                                                           | 1   |
| 91                      | 5111.096 | plate                                                           | 1   |
| 92                      | 6370.420 | el.start.plate                                                  | 1   |
| 93                      | 6360.073 | plate                                                           | 1   |
| 94                      | 7625.062 | washer diam. 6,5                                                | 4   |
| 95                      | 6055.055 | hollowstud                                                      | 4   |
| 96                      | 3203.050 | selflocking nut M 6                                             | 4   |
| 97                      | 9730.315 | screw M 7 X 1 X 35                                              | 1   |
| 98                      | 1472.057 | rewind starting                                                 | 1   |
| 99                      | 2610.060 | front cover                                                     | 1   |
| 100                     | 9730.340 | screw M 5 X 10                                                  | 1   |
| 101                     | «-----»  | tooth recovery spring                                           | 0   |
| 103                     | 7625.213 | washer diam. 6                                                  | 1   |
| 104                     | 9732.016 | screw M 6 X 40                                                  | 1   |
| 106                     | 7980.063 | cup                                                             | 1   |

**Group: 6LD**

**Engine: 6LD 400 Drawing: F**

**COOLING SYSTEM/STARTING**

| POS. | CODE     | DESCRIPTION    | Qty |
|------|----------|----------------|-----|
| 107  | 6275.102 | spring plate   | 1   |
| 108  | 7470.003 | filler         | 1   |
| 109  | 9730.325 | screw M 5 X 10 | 4   |

