

**CONTROLS**

POS.	CODE	DESCRIPTION	Qty
1	1760.028	bolt M 6 X 1 X 35	1
1a	9765.169	screw M 6 X 40 (EPA)	1
2	1760.028	bolt M 6 X 1 X 35	1
3	3240.153	nut M 6	1
3a	3300.237	nut (EPA type)	1
4	9730.009	screw M 6 X 12	4
5	3240.164	nut M 8	1
6	«-----»	see Pos. 16/64	0
7	3240.019	nut M 8 alpha brass	2
8	9180.193	wire end	1
10	5060.008	support	1
12	4190.103	locking nut	1
13	«-----»	see Pos. 32	0
14	3240.153	nut M 6	1
15	8430.004	tapper pin	1
16	2516.105	control stop ass.y	1
16a	«-----»	cover (see Pos. I 16/I 64)	0
16b	2700.046	cover	1
17	8430.004	tapper pin	1
18	4431.205	gasket	1
19	«-----»	recovery spring	0
20	1200.052	O ring	1
21	«-----»	see Pos. 16/64	0
23	3240.164	nut M 8	1
24	«-----»	recovery spring	0
25	1200.052	O ring	1
26	3203.048	nut M 6	1
27	7625.070	washer diam. 6	1
28	«-----»	see Pos. 39	0
31	9730.009	screw M 6 X 12	4
32	2516.167	REMOTE ACCEL.CONTROL with lever pos.13a	1
32	2516.168	REMOTE ACCEL.CONTROL with lever pos.13c	1
32	2700.041	throttle cover	1
33	4431.206	gasket	1
34	8400.048	taper pin	2
35	«-----»	see Pos. 32	0
36	1970.203	sleeve	2
37	«-----»	see Pos. 39	0
39	5200.900	governor lever 2201-2900	1
39	5200.901	governor lever 1500 R.P.M.	1
39	5200.902	governor lever 1800-2200	1
39	5200.906	governor lever 3000 R.P.M.	1
40	6140.408	lever shaft	1
41	9730.198	screw M 6	1
42	4670.021	copper gasket diam.18	1
43	3240.152	device nut	1
44	2380.522	locked torque device (1500/1800 R.p.M.)	1
44	8576.119	eXtra fuel device 2800 -> 3000 Rpm/1'	1
44	8576.120	eXtra fuel device -> 2800 Rpm/1'	1
45	1541.119	spring brace 2201-2900 R.P.M.	1
45	1541.120	spring brace 1800-2200 R.P.M.	1
45	1541.201	spring brace 3000 R.P.M.	1
45	1541.218	spring brace 1500 R.P.M.	1

Group: CHD-SUPERCHD
Engine: LDW 2004 Drawing: I

CONTROLS			
POS.	CODE	DESCRIPTION	Qty
46	«-----»	gover.lever spring - see Pos ./ 39/63/76	0
47	5801.208	device spring	1
48	1240.002	circlip diam. 8	1
49	9730.010	screw M 6 X 16	3
50	«-----»	see remarks	0
51	8460.055	locating dowel	2
52	1240.002	circlip diam. 8	1
54	5830.119	nut	1
56	6000.016	nut	1
57	1760.128	adjusting bolt M 6X25	1
58	7625.124	washer diam. 6,5	1
59	3240.153	nut M 6	1
60	1380.040	injection pump control rod	1
61	3440.027	control stop	1
62	8545.539	bracket	1
63	5201.195	govern.lever 2500 R.p.m.	1
64	2516.177	contr.stop with antihunting device	1
67	9245.166	tie rod	1
69	7481.070	nail	2
70	5168.071	safety plate	1
71	5168.070	safety plate	1
73	5655.135	governor spring 2800÷3000 R.P.M.	1
73	5655.154	governor spring 1500÷1800÷2200 R.P.M.	1
73	5655.156	governor spring 1500 R.P.M.	1
74	5655.129	governor spring 3000 R.P.M.	1
74	5655.135	governor spring 2800÷3000 R.P.M.	1
74	5655.154	governor spring 1500÷1800÷2200 R.P.M.	1

