



## FUEL SYSTEM

| POS. | CODE     | DESCRIPTION                                    | Qty |
|------|----------|------------------------------------------------|-----|
| 2    | 9730.313 | fix.screw                                      | 6   |
| 3    | 4750.014 | delivery pipe seal                             | 1   |
| 4    | 3240.164 | nut M 8                                        | 2   |
| 5    | 7555.029 | washer diam. 8                                 | 2   |
| 6    | 6780.049 | intake stud M 8 X 20 (36)                      | 2   |
| 7    | 6585.097 | feed pump                                      | 1   |
| 8    | 1200.087 | O ring 3150                                    | 1   |
| 9    | «-----»  | push rod (4200-> R.P.M.) unified with std type | 0   |
| 9    | 7200.721 | drive rod                                      | 1   |
| 10   | 1200.286 | seal ring 9,25X1,78                            | 6   |
| 11   | 3240.164 | nut M 8                                        | 6   |
| 12   | 6780.135 | stud                                           | 6   |
| 13   | 7555.029 | washer diam. 8                                 | 6   |
| 14   | 1410.112 | tapped                                         | 3   |
| 15   | «-----»  | screw                                          | 0   |
| 16   | 9680.037 | bleeding valve                                 | 3   |
| 17   | 5801.274 | delivery valve spring                          | 3   |
| 18   | 9672.107 | delivery valve                                 | 3   |
| 19   | «-----»  | seal ring                                      | 0   |
| 20   | 6578.211 | injection plunger                              | 3   |
| 21   | «-----»  | locking nut                                    | 0   |
| 23   | 5755.113 | tappet spring                                  | 3   |
| 24   | «-----»  | push rod - see Pos. F 25                       | 0   |
| 25   | 6590.285 | nozzle-injection pump                          | 3   |
| 26   | «-----»  | body                                           | 0   |
| 27   | 8335.142 | adj.spacer 2,00                                | 3   |
| 27   | 8335.143 | adj.spacer 1,90                                | 3   |
| 27   | 8335.144 | adj.spacer 1,80                                | 3   |
| 27   | 8335.145 | adj.spacer 1,70                                | 3   |
| 27   | 8335.146 | adj.spacer 1,60                                | 3   |
| 27   | 8335.147 | adj.spacer 1,50                                | 3   |
| 27   | 8335.148 | adj.spacer 1,40                                | 3   |
| 27   | 8335.149 | adj.spacer 1,30                                | 3   |
| 27   | 8335.150 | adj.spacer 1,20                                | 3   |
| 27   | 8335.151 | adj.spacer 1,10                                | 3   |
| 27   | 8335.152 | adj.spacer 1,00                                | 3   |
| 28   | «-----»  | pressure spring - no longer avail.             | 0   |
| 29   | 1420.048 | drive rod                                      | 3   |
| 30   | 3527.220 | spacer                                         | 3   |
| 31   | «-----»  | filler - no longer available                   | 0   |
| 32   | 4760.015 | valve gasket                                   | 3   |
| 33   | «-----»  | filler                                         | 0   |
| 35   | 1200.277 | seal ring 20,35X1,78                           | 3   |
| 36   | 5375.017 | governor sleeve                                | 3   |
| 37   | 9730.206 | screw TCEI M 4 X 12                            | 12  |
| 38   | 6410.096 | lower ret.                                     | 3   |
| 39   | «-----»  | circlip diam. 19 - see Pos. F 25               | 0   |
| 40   | 5989.007 | spark arrestor                                 | 3   |
| 41   | 1200.213 | O ring 26,70X1,78                              | 3   |
| 42   | «-----»  | locking nut                                    | 0   |
| 43   | 6531.436 | nozzle                                         | 3   |
| 44   | 1901.030 | union bolt M 10                                | 2   |
| 45   | 4670.059 | copper gasket diam.10                          | 2   |

**Group: FOCS-SUPERFOCS**  
**Engine: LDW 903 Drawing: F**

**FUEL SYSTEM**

| POS. | CODE     | DESCRIPTION                               | Qty |
|------|----------|-------------------------------------------|-----|
| 47   | 1901.030 | union bolt M 10                           | 1   |
| 48   | 1570.045 | filler cap M 14                           | 1   |
| 49   | 3587.119 | electro-valve                             | 1   |
| 49   | 3587.135 | electro-valve 24V                         | 1   |
| 51   | 3730.073 | FUEL FILTER                               | 1   |
| 51b  | 3730.103 | FUEL FILTER                               | 1   |
| 52   | 4670.059 | copper gasket diam.10                     | 2   |
| 53   | 4670.061 | copper gasket diam.14                     | 2   |
| 54   | 9375.857 | del.pipe mm 680                           | 1   |
| 54   | 9375.859 | del.pipe mm 1000                          | 1   |
| 54   | 9375.868 | del.pipe mm 500                           | 1   |
| 55   | 9375.673 | fuel pipe (mm 416)                        | 1   |
| 55   | 9375.853 | fuel pipe mm 1000                         | 1   |
| 56   | 2175.256 | fuel filter cartridge                     | 1   |
| 57   | 4670.082 | copper gasket diam.14 X 1                 | 3   |
| 58   | «-----»  | lockpin                                   | 0   |
| 60   | 4670.061 | copper gasket diam.14                     | 2   |
| 61   | 1901.032 | union bolt M 14                           | 1   |
| 62   | 1200.287 | O ring 25,12X1,78                         | 3   |
| 63   | 4760.038 | gasket                                    | 3   |
| 64   | 9375.995 | delivery pipe                             | 1   |
| 66   | 1780.004 | bolt M 10 X 1,5 X 22                      | 2   |
| 67   | 7625.019 | washer diam.10                            | 2   |
| 68   | 7645.006 | washer diam. 8                            | 2   |
| 69   | 8545.675 | filter support                            | 1   |
| 70   | 9730.026 | screw M 8 X 20                            | 2   |
| 71   | 7270.138 | banjo union diam.10                       | 1   |
| 73   | 3730.128 | FUEL FILTER                               | 1   |
| 74   | 2175.046 | fuel filter cartridge                     | 1   |
| 75   | 3730.126 | FUEL FILTER                               | 1   |
| 76   | 3730.093 | FUEL FILTER witht water bleeding          | 1   |
| 78   | 2175.143 | fuel filter cartridge with water bleeding | 1   |
| 79   | 3730.173 | FUEL FILTER witht water separator         | 1   |
| 80   | 2175.042 | fuel filter cartridge                     | 1   |
| 81   | 3616.082 | fuel tank strap                           | 2   |
| 82   | 9600.057 | rubber spacer                             | 4   |
| 83   | 9043.025 | fuel tank cap                             | 1   |
| 84   | 9761.001 | screw M 4 X 0,7 X 12                      | 6   |
| 85   | 5055.023 | plate                                     | 1   |
| 86   | 4776.040 | gasket                                    | 1   |
| 87   | 9730.139 | screw M 6 X 60                            | 2   |
| 88   | 1557.019 | drilled block                             | 2   |
| 89   | 1557.020 | threaded block                            | 2   |
| 90   | 8042.024 | fuel tank saddle                          | 1   |
| 91   | 8636.001 | vibration-damping                         | 4   |
| 92   | 6370.515 | tank plate                                | 1   |
| 93   | 8315.016 | rubber shim                               | 1   |
| 94   | 8103.021 | fuel tank 15 liters                       | 1   |
| 95   | 4906.008 | fuel gauge (mm 193) 15/29 lt              | 1   |
| 96   | 9043.092 | fuel tank cap                             | 1   |
| 97   | 8866.067 | support                                   | 2   |
| 98   | 4701.029 | rubber shim                               | 4   |
| 99   | 9245.076 | stay bolt                                 | 2   |

**Group: FOCS-SUPERFOCS**  
**Engine: LDW 903 Drawing: F**

| FUEL SYSTEM |          |                            |     |
|-------------|----------|----------------------------|-----|
| POS.        | CODE     | DESCRIPTION                | Qty |
| 100         | 8635.059 | vibration-damping          | 4   |
| 101         | 8103.308 | FUEL TANK (29 liters)      | 1   |
| 102         | 8866.066 | support                    | 2   |
| 103         | 4701.030 | rubber shim                | 4   |
| 104         | 9372.023 | fuel hose mm 2000          | 1   |
| 118b        | 9375.959 | bleeding pipe mm 530       | 1   |
| 118c        | 9375.266 | bleeding pipe (mm 1000)    | 1   |
| 119         | 2185.878 | el.valve connctection wire | 1   |
| 120         | «-----»  | transparent cap            | 0   |
| 134         | 3630.050 | clamp dia 9-11             | 1   |
| 134a        | 3630.217 | clamp dia 11,5-13,5        | 1   |
| 139         | 9680.049 | no retur fuel-valve        | 1   |
| 140         | 4670.061 | copper gasket diam.14      | 2   |
| 141         | 2471.006 | collar                     | 1   |

# FOCS SUPERFOCS

