

**LOMBARDINI**

A KOHLER COMPANY

Group: FOCS-SUPERFOCS

Engine: LDW 903 Drawing: H

LUBRICATING SYSTEM

POS.	CODE	DESCRIPTION	Qty
1	6975.292	driving pulley	1
2	1213.343	seal ring 32X50X6	1
3	4670.060	copper gasket diam.12	1
4	9015.005	plug	1
5	5625.008	pressure valve spring	1
6	6495.045	drive rod	1
7	«-----»	no more fitted	0
9	9800.061	screw M 6 X 16	3
11	7750.105	oil pump rotors	1
12	1200.030	rubber oil seal	1
14	1770.007	bolt M 8 X 1,25 X 30	1
15	1200.274	oil seal diam. 8,00	1
17	9732.074	screw M 8 X 20	6
18	6605.096	OIL PUMP	1
19	1200.292	O ring	1
20	«-----»	see Pos. 18	0
21	4580.216	gasket	1
22	1200.266	rubber oil seal	2
22a	1200.034	O ring 105	2
23	1400.318	dipstick (mm 101)	1
23	1400.456	dipstick (mm 83)	1
24	7500.018	washer	18
25	1760.130	bolt M 6 X 1 X 12	18
28	4670.088	copper gasket 18X24X1	2
29	9040.024	plug M 18 h = 22	2
30	7625.008	washer diam. 6,4	1
31	1760.130	bolt M 6 X 1 X 12	1
32	7265.021	oil filter connector	1
33	2175.107	oil filter cartridge (mm 59)	1
34	«-----»	lockpin	0
36	4431.120	gasket	1
37	9485.272	scavenge oil pipe	1
40	6645.538	oil pan (l 2,5)	1
42	9330.086	dipstick guard	1
43	1400.297	dipstick on cyl.head mm 426	1
43	1400.338	dipstick on cyl.head mm 449	1
43	1400.341	dipstick on rocker arm cover mm 548	1
43	1400.342	dipstick on rocker arm cover mm 571	1
43	1400.474	dipstick on cyl.head mm 461	1
49	9865.174	screw	2
50	9330.092	dipstick guard on rocker arm cover	1
53	3527.395	spacer mm 68 for oil pan	1
53	3527.402	spacer mm 40 for oil pan	1
75	1200.034	O ring 105	2
88	2501.158	hollowstud	1
88	3500.037	hollowstud mm 68 for spacer mm 68 for oil pan	1

H FOCS SUPERFOCS

