

**LOMBARDINI**

A KOHLER COMPANY

Group: FOCS-SUPERFOCS

Engine: LDW 1003 Drawing: H

**LUBRICATING SYSTEM**

| POS. | CODE     | DESCRIPTION                                   | Qty |
|------|----------|-----------------------------------------------|-----|
| 1    | 6975.292 | driving pulley                                | 1   |
| 2    | 1213.343 | seal ring 32X50X6                             | 1   |
| 3    | 4670.060 | copper gasket diam.12                         | 1   |
| 4    | 9015.005 | plug                                          | 1   |
| 5    | 5625.008 | pressure valve spring                         | 1   |
| 6    | 6495.045 | drive rod                                     | 1   |
| 9    | 9800.061 | screw M 6 X 16                                | 3   |
| 11   | 7750.105 | oil pump rotors                               | 1   |
| 12   | 1200.030 | rubber oil seal                               | 1   |
| 14   | 1770.007 | bolt M 8 X 1,25 X 30                          | 1   |
| 15   | 1200.274 | oil seal diam. 8,00                           | 1   |
| 17   | 9732.074 | screw M 8 X 20                                | 6   |
| 18   | 6605.096 | OIL PUMP                                      | 1   |
| 19   | 1200.292 | O ring                                        | 1   |
| 20   | «-----»  | see Pos. 18                                   | 0   |
| 21   | 4580.216 | gasket                                        | 1   |
| 22   | 1200.266 | rubber oil seal                               | 2   |
| 22a  | 1200.034 | O ring 105                                    | 2   |
| 23   | 1400.321 | dipstick mm (113)                             | 1   |
| 23   | 1400.456 | dipstick (mm 83)                              | 1   |
| 25   | 1760.130 | bolt M 6 X 1 X 12                             | 18  |
| 28   | 4670.088 | copper gasket 18X24X1                         | 2   |
| 29   | 9040.024 | plug M 18 h = 22                              | 2   |
| 31   | 1760.130 | bolt M 6 X 1 X 12                             | 1   |
| 32   | 7265.021 | oil filter connector                          | 1   |
| 33   | 2175.107 | oil filter cartridge (mm 59)                  | 1   |
| 35   | «-----»  | see Pos. C 10                                 | 0   |
| 36   | 4431.120 | gasket                                        | 1   |
| 37   | 9485.272 | scavenge oil pipe                             | 1   |
| 40   | 6645.538 | oil pan (l 2,5)                               | 1   |
| 40   | 6645.704 | oil pan (l 2,5) fitted for oil alert device   | 1   |
| 42   | 9330.086 | dipstick guard                                | 1   |
| 43   | 1400.297 | dipstick on cyl.head mm 426                   | 1   |
| 43   | 1400.474 | dipstick on rocker arm cover mm 458           | 1   |
| 49   | 9865.174 | screw                                         | 2   |
| 75   | 1200.034 | O ring 105                                    | 2   |
| 88   | 2501.158 | hollowstud                                    | 1   |
| 88   | 3500.037 | hollowstud mm 68 for spacer mm 68 for oil pan | 1   |
| 93   | 1755.001 | bolt M 5 X 0,8 X 8                            | 1   |
| 94   | 7565.003 | washer diam. 5                                | 1   |
| 95   | 6927.372 | guard                                         | 1   |
| 96   | 1200.016 | O ring 137                                    | 1   |
| 97   | 3440.060 | oil alert device                              | 1   |
| 98   | 6370.631 | plate                                         | 1   |
| 99   | 7625.008 | washer diam. 6,4                              | 2   |
| 100  | 1760.001 | bolt M 6 X 1 X 10                             | 2   |

