

**LOMBARDINI**

A KOHLER COMPANY

Group: FOCS-SUPERFOCS

Engine: LDW 1204 Drawing: F

FUEL SYSTEM

POS.	CODE	DESCRIPTION	Qty
2	9730.313	fix.screw	8
3	4750.014	delivery pipe seal	1
4	3240.164	nut M 8	2
5	7555.029	washer diam. 8	2
6	6780.049	intake stud M 8 X 20 (36)	2
7	6585.096	feed pump	1
7	6585.097	feed pump	1
8	1200.087	O ring 3150	1
9	«-----»	push rod (4200-> R.P.M.) unified with std type	0
9	7200.721	drive rod	1
10	1200.286	seal ring 9,25X1,78	8
11	3240.164	nut M 8	8
12	6780.135	stud	8
13	7555.029	washer diam. 8	8
14	1410.112	tapped	4
15	«-----»	screw	0
16	9680.037	bleeding valve	4
17	5801.274	delivery valve spring	4
18	9672.107	delivery valve	4
19	«-----»	seal ring	0
20	6578.211	injection plunger	4
21	«-----»	locking nut	0
23	5755.113	tappet spring	4
24	«-----»	push rod - see Pos. F 25	0
25	6590.285	nozzle-injection pump	4
26	«-----»	body	0
27	8335.142	adj.spacer 2,00	4
27	8335.143	adj.spacer 1,90	4
27	8335.144	adj.spacer 1,80	4
27	8335.145	adj.spacer 1,70	4
27	8335.146	adj.spacer 1,60	4
27	8335.147	adj.spacer 1,50	4
27	8335.148	adj.spacer 1,40	4
27	8335.149	adj.spacer 1,30	4
27	8335.150	adj.spacer 1,20	4
27	8335.151	adj.spacer 1,10	4
27	8335.152	adj.spacer 1,00	4
28	«-----»	pressure spring - no longer avail.	0
29	1420.048	drive rod	4
30	3527.220	spacer	4
31	«-----»	filler - no longer available	0
32	4760.015	valve gasket	4
33	«-----»	filler	0
35	1200.277	seal ring 20,35X1,78	4
36	5375.017	governor sleeve	4
37	9730.206	screw TCEI M 4 X 12	16
38	6410.096	lower ret.	4
39	«-----»	circlip diam. 19 - see Pos. F 25	0
40	5989.007	spark arrestor	4
41	1200.213	O ring 26,70X1,78	4
42	«-----»	locking nut	0
43	6531.436	nozzle	4
44	1901.030	union bolt M 10	2

Group: FOCS-SUPERFOCS
Engine: LDW 1204 Drawing: F

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
45	4670.059	copper gasket diam.10	2
47	1901.030	union bolt M 10	1
48	1570.045	filler cap M 14	1
49	3587.119	electro-valve	1
49	3587.135	electro-valve 24V	1
51	3730.073	FUEL FILTER	1
51b	3730.103	FUEL FILTER	1
52	4670.059	copper gasket diam.10	2
53	4670.061	copper gasket diam.14	2
54	9375.857	del.pipe mm 680	1
54	9375.859	del.pipe mm 1000	1
54	9375.868	del.pipe mm 500	1
55	9375.673	fuel pipe (mm 416)	1
55	9375.853	fuel pipe mm 1000	1
56	2175.256	fuel filter cartridge	1
57	4670.082	copper gasket diam.14 X 1	4
58	«-----»	lockpin	0
60	4670.061	copper gasket diam.14	2
61	1901.032	union bolt M 14	1
62	1200.287	O ring 25,12X1,78	4
63	4760.038	gasket	4
65	9375.988	delivery pipe	1
66	1780.004	bolt M 10 X 1,5 X 22	2
67	7625.019	washer diam.10	2
68	7645.006	washer diam. 8	2
69	8545.675	filter support	1
70	9730.026	screw M 8 X 20	2
71	7270.138	banjo union diam.10	1
73	3730.128	FUEL FILTER	1
74	2175.046	fuel filter cartridge	1
75	3730.126	FUEL FILTER	1
76	3730.093	FUEL FILTER witht water bleeding	1
76a	3730.150	FUEL FILTER witht water bleeding	1
78	2175.143	fuel filter cartridge with water bleeding	1
78a	2175.053	fuel filter cartridge	1
79	3730.173	FUEL FILTER witht water separator	1
80	2175.042	fuel filter cartridge	1
81	3616.082	fuel tank strap	2
82	9600.057	rubber spacer	4
83	9043.025	fuel tank cap	1
84	9761.001	screw M 4 X 0,7 X 12	6
85	5055.023	plate	1
86	4776.040	gasket	1
87	9730.139	screw M 6 X 60	2
88	1557.019	drilled block	2
89	1557.020	threaded block	2
90	8042.024	fuel tank saddle	1
91	8636.001	vibration-damping	4
92	6370.515	tank plate	1
93	8315.016	rubber shim	1
94	8103.021	fuel tank 15 liters	1
95	4906.008	fuel gauge (mm 193) 15/29 lt	1
96	9043.092	fuel tank cap	1

Group: FOCS-SUPERFOCS
Engine: LDW 1204 Drawing: F

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
97	8866.067	support	2
98	4701.029	rubber shim	4
99	9245.076	stay bolt	2
100	8635.059	vibration-damping	4
101	8103.308	FUEL TANK (29 liters)	1
102	8866.066	support	2
103	4701.030	rubber shim	4
104	9372.023	fuel hose mm 2000	1
118b	9375.959	bleeding pipe mm 530	1
118c	9375.266	bleeding pipe (mm 1000)	1
119	2185.878	el.valve connctection wire	1
120	«-----»	transparent cap	0
134	3630.050	clamp dia 9-11	1
134a	3630.217	clamp dia 11,5-13,5	1
139	9680.049	no retur fuel-valve	1
140	4670.061	copper gasket diam.14	2
141	2471.006	collar	1

FOCS SUPERFOCS

